

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product

“BRITON 376 (See ANNEX A) **377** (See ANNEX B) **378** (See ANNEX C) **379** (See ANNEX D)
BOSS PH.902 (See Annex A) **PH.903** (See Annex B) **PH.901** (See Annex C)
PH.904 (See Annex D) **Series” Panic Exit Devices**

Intended use: **For use on single and double leaf escape panic doors, including fire resisting doors & Locked doors on escape routes.**

Essential Characteristics	Performance	Harmonised Technical Specification
Mechanical Test Evidence : WIL 539076 / WIL 539077 / WIL 539078 / WIL 539079 / WIL 541902 Iss 2 & WIL 541969 Fire Test Evidence : WF 127579 / WF 417359 / WF 417361 Iss 2 / WF 539511/R / WF 544056 Iss 1 & WF 542544/R Iss 2		
Clause 4.2.1 Ability to release (for doors on panic routes) Release function Panic exit device mounting Exposed edges and corners Double doorset Single doorset Bar installation Bar length Bar projection Bar end Operating bar face Test rod Door face gap Accessible gap Door free movement Top vertical bolt Keepers Keepers dimensions Door mass and dimensions Outside access device Release forces Security requirement	< 1 sec Pass > 0,5 mm Pass Pass Z < 150 mm > 60% W < 100mm Pass > 18 mm Pass > 25 mm Pass Pass Pass – (Annex A & Annex B Only) Pass Pass – (Annex A & Annex B Only) Door mass ≤ 200 Kg, door height ≤ 2500 mm, door width ≤ 1300 mm Pass < 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N Grade 2	EN 1125:2008
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on panic routes) Corrosion resistance Temperature range Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance –Horizontal bar Abuse resistance –Vertical rod Final examination	Grade 3 : 96 h Operating forces at -10 C° and +60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 1 000 N 500 N – (Annex A & Annex B Only) < 80 N with the door unloaded, and < 220 N with the door loaded with 1 000 N	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Essential Characteristics	Performance	Harmonised Technical Specification
Clause 4.2.1 Self closing ability C (for fire/smoke doors on panic routes) Re-engagement force	< 50 N	EN 1125:2008
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on panic routes) Durability Re-engagement force	Grade 7: 200 000 cycles < 50 N	
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on panic routes) Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B: Suitable for use on fire/smoke door assemblies.	
Clause 4.1.25 Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Product Codes	Single Door (Standard Keeper)	Double Door (Standard Keepers)	Approved with Alternate Strike or Keeper			
			Briton 378 DDS Boss PH901 DDS	Briton 376 MDS Boss PH902 MDS	Briton 378 MDS Boss PH901 MDS	Briton 379 MDS Boss PH904 MDS
ANNEX A						
Briton 376	√	√	-----	√	-----	-----
Briton 376D	√	√	-----	√	-----	-----
Briton 376 with 380/1011/SE	√	√	-----	√	-----	-----
Boss PH.902 with PH9/1011/SIL	√	√	-----	√	-----	-----
Briton 376 with 370PLTM	√	√	-----	√	-----	-----
Boss PH.902 with PH900PLTM	√	√	-----	√	-----	-----
Briton 376 with 376/1021/SE	√	√	-----	√	-----	-----
Boss PH.902 with PH9/1021/SIL	√	√	-----	√	-----	-----
Briton 376 with 376/1021/SE & 370PLTM	√	√	-----	√	-----	-----
Boss PH.902 with PH9/1021/SIL & PH900PLTM	√	√	-----	√	-----	-----
Briton 376M	√	√	-----	√	-----	-----
Briton 376M with 370PLTM	√	√	-----	√	-----	-----
Boss PH.902	√	√	-----	√	-----	-----
ANNEX B						
Briton 377	-----	√	√	√	√	-----
Briton 377D	-----	√	√	√	√	-----
Briton 377M	-----	√	√	√	√	-----
Boss PH.903	-----	√	√	√	√	-----
ANNEX C						
Briton 378	√	√	√	-----	√	-----
Briton 378D	√	√	√	-----	√	-----
Briton 378 with 376/1021/SE	√	√	√	-----	√	-----
Boss PH.901 with PH9/1021/SIL	√	√	√	-----	√	-----
Briton 378M	√	√	√	-----	√	-----
Boss PH.901	√	√	√	-----	√	-----
ANNEX D						
Briton 379.N	√	√	-----	-----	-----	√
Briton 379D.N	√	√	-----	-----	-----	√
Briton 379M.N	√	√	-----	-----	-----	√
Briton 379.N With 380/1011/SE	√	√	-----	-----	-----	√
Boss PH.904	√	√	-----	-----	-----	√
Boss PH.904 with PH9/1011/SIL	√	√	-----	-----	-----	√
Outside Access Devices						
Model Number	Description					
Briton 1413.LE	Lever outside access device (Suitable for use with all Briton devices)					
Briton 1413.KE	Knob outside access device (Suitable for use with all Briton devices)					
Boss OAD.900LE	Lever outside access device (Suitable for use with all Boss devices)					
Boss OAD.900KE	Knob outside access device (Suitable for use with all Boss devices)					

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Accessories	
Briton 376/1001/SE	Main Box Assembly
Briton 376/1011/SE	End Box Assembly
Briton 378/1001/SE	Latch Box Assembly
Briton 376/413/SE	Crossbar - New Oval type
Briton 376/416/50	End Plug
Briton 376/931/SE	Pullman Assembly x 1 for replacement
Briton 379/931/SS	Nightlatch lock case
Briton 379/1001/SE	Mortice latch Box Assembly
Boss PH902/1001/SIL	Main Box Assembly
Boss PH902/1011/SIL	End Box Assembly
Boss PH901/1001/SIL	Latch Box Assembly
Boss PH9/413/SIL	Crossbar - New Oval type
Boss PH9/416/50	End Plug
Boss PH9/931/SIL	Pullman Assembly x 1 for replacement
Boss PH904/931/SS	Nightlatch lock case
Boss PH904/1001/SIL	Mortice latch Box Assembly
Briton 376ELTS/SE	Extra Long Shoot Bolts
Briton 376FFKP/ZP	Flush Face Keeper Plate
Briton 376/330/00	'Push Bar to Open' Label
Briton PH902ELTS/SIL	PH902 Extra Long Shoot Bolts
Briton PH902FFKP/ZP	PH902 Flush Face Keeper Plate
Briton PH9/330/00	'Push Bar to Open' Label
Cisa OG500.50.12 SD1	Cisa C2000 Rim Cylinder nickle plated brass (For use on 378 only)
Cisa OG500.50.00 SD1	Cisa C2000 Rim Cylinder sanded brass (For use on 378 only)
Fixing Kits	
Briton 370PT	370 series Panic Bolt fixing kit (376/372/377) Timber Door
Briton 370PM	370 series Panic Bolt fixing kit (376/372/377) Metal Door
Briton 370PLT	370 series Emergency Exit latch fixing kit (1438/378/377) Timber Door
Briton 370PLM	370 series Emergency Exit latch fixing kit (1438/378/377) Metal Door
Briton 370EMT	370 series Emergency mortice latch fixing kit (379.N/389.N) Timber/Metal door
Briton 370PLTM	370 Series Panic Bolt Pullman fixing kit (376/372) Timber/Metal x2 pullmans plus instruction plus strikes/screws
Boss PH900PT	PH900 series Panic Bolt fixing kit (PH902/PH905/PH903) Timber Door
Boss PH900PM	PH900 series Panic Bolt fixing kit (PH902/PH905/PH903) Metal Door
Boss PH900PLT	PH900 series Emergency Exit latch fixing kit (PH906/PH901/PH903) Timber Door
Boss PH900PLM	PH900 series Emergency Exit latch fixing kit (PH906/PH901/PH903) Metal Door
Boss PH900EMT	PH900 series Emergency mortice latch fixing kit (PH904/PH907) Timber door
Boss PH900PLTM	PH900 Series Panic Bolt Pullman fixing kit (PH902/PH905) Timber/Metal x2 pullmans plus instruction plus strikes/screws

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Screw Packs	
Briton 376/920/ZP	370 Series (376, 372, 377) Timber door screw pack
Briton 376/919/ZP	370 Series (376M, 372M, 377M) Metal door screw pack
Briton 378/920/ZP	370 Series (378, 1438, 377) Timber door screw pack
Briton 378/919/ZP	370 Series (378M, 1438M, 377M) Metal door screw pack
Briton 379/940/ZP	370 Series (379, 389) Timber door screw pack
Briton 379/919/ZP	370 Series (379M, 389M) Metal door screw pack
Briton 376/940/ZP	376 Pullman timber door screw pack
Briton 376/949/ZP	376 Pullman Metal door screw pack
Boss PH902/920/ZP	PH900 Series (PH902, PH905, PH903) Timber door screw pack
Boss PH902/919/ZP	PH900 Series (PH902M, PH905M, PH903M) Metal door screw pack
Boss PH901/920/ZP	PH900 Series (PH901, PH906, PH903) Timber door screw pack
Boss PH901/919/ZP	PH900 Series (PH901M, PH906M, PH903M) Metal door screw pack
Boss PH904/940/ZP	PH900 Series (PH904, PH907) Timber door screw pack
Boss PH904/919/ZP	PH900 Series (PH904M, PH907M) Metal door screw pack
Boss PH902/940/ZP	PH902 Pullman timber door screw pack
Boss PH902/949/ZP	PH902 Pullman Metal door screw pack

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AAA0011

Placed on the market under the Name of:

**Allegion (UK) Ltd
35 Rocky Lane
Birmingham
West Midlands
B6 5RQ
United Kingdom**

and produced in the manufacturing plant:

E014110-19

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 1125: 2008

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **26/10/2020** and reissued **30/03/2026** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **02/04/2029**

ERO Project Reference: **ERO 034621 P3104**



**Pascal Coget
European Certification –General Manager**

CSF408-NL 8.0