

# PH.9 SERIES

## PANIC & EMERGENCY EXIT HARDWARE

### PH.905 EMERGENCY EXIT WITH VERTICAL BOLTS

#### INTRODUCTION


The BOSS PH.905 push pad emergency exit device with double vertical bolts is suitable for single doors up to 1300mm wide and 2500mm high. Products conforming to EN 179 are only intended for use by personnel who are fully aware of escape routes and have been trained to operate these devices.

#### IMPORTANT NOTE:

**If you are in any doubt at all, ALWAYS use products that conform to EN 1125.**

#### FEATURES & FUNCTIONS

- Suitable for all single doors, non rebated double doors and in combination with 378DDS double door strike and BOSS PH.906 emergency latch on the inactive leaf of rebated double doors
- Designed to satisfy emergency exit applications
- Suitable for fire & smoke doors 665mm to 1300mm wide
- Site reversible - easy to hand on site
- Two-point locking for extra security
- Anti-thrust latches prevent forced latch retraction
- Adjustable top and bottom shoots
- Tested in excess of 200,000 cycles



EN Classification  
**3 7 6 B 1 3 2 2**  
**AA**




#### CERTIFICATION

- CE Marked to EN 179 (2812-CPR-ABB0020)
- Certifiere Approved (CF5506)
- Fire tested to EN 1634-1 for use on fire doors up to 2hr timber (1hr timber when used with Outside Access Devices) / 4hr steel
- Environmental Product Declaration in accordance with ISO 14025 and EN 15803
- DoP available at [www.bosssdoorcontrols.com](http://www.bosssdoorcontrols.com)

#### APPLICATIONS

Suitable for all single doors, non rebated double doors and in combination with BOSS PH.901 double door strike and BOSS PH.906 emergency latch on the inactive leaf of rebated double doors.



**Boss Door Controls Ltd**  
3 & 4 Rutherford Square, Brucefield Industry Park,  
Livingston, West Lothian EH54 9BU

T: +44 (0) 1506 467 477  
E: [boss.sales@allegion.com](mailto:boss.sales@allegion.com)




[www.bosssdoorcontrols.com](http://www.bosssdoorcontrols.com)

## PH.905 EMERGENCY EXIT WITH VERTICAL BOLTS

PRODUCT FEATURES	PRODUCT REFERENCES
	<b>PH.905</b>
UKCA & CE marked	■
Panic exit device to EN 1125	
Emergency exit device to EN 179	■
Device type	Emergency push pad
Locking points	Vertical bolts
Suitable for timber or metal doors	Timber
Suitable for single doors	■
Suitable for double door combinations	★
Min. / Max. door width (per leaf)	N/A
Push bar cut on site	N/A
Site reversible	■
Finishes available	SE
UKCA / CE Classification	3 7 6 B 1 3 4 2 B A

- Standard.
- Available as an option/variant.
- ★ Used as a pair on non rebated doors or in combination with a BOSS PH.901 rim latch fitted to the first opening leaf of rebated double doors.



## PH.905 EMERGENCY EXIT WITH VERTICAL BOLTS - ACCESSORIES

A range of additional or alternative components is available for the PH.9 Series of exit hardware.



### 376ELTS - EXTRA LONG TOP SHOOT

Extra long top shoots are designed to be used on doors that require the push bar to be in a lower position e.g. schools. It can also be used on doors that exceed 2500mm up to 3350mm high.



### 376MDS - METAL DOOR STRIKE

For vertical panic bolts. Comprises 2 strike plates and 1 trip plate to activate the top tripper.



### OAD.900LE - OUTSIDE ACCESS DEVICE

Provide a strong and durable means of accessing the door from the outside. Lever operated.



### OAD.900KE - OUTSIDE ACCESS DEVICE

Provide a strong and durable means of accessing the door from the outside. Knob operated.



### 9260 - DIGITAL CODE LOCK

An easy to fit light duty mechanical push button lock with lever operation. Suitable for low traffic applications on internal and external doors.



### 378DDS - DOUBLE DOOR STRIKE

For use on double rebated doors with a rim panic latch on the first opening leaf and a vertical bolt on the second opening leaf.



### 376FFKP - FLUSH FACE KEEPER PLATE

For flush fitting doors and frames a surface mounted flush face keeper plate can be used to secure the bolt.




### 370PLTM - PULLMAN LATCHES

Pullman latches offer increased security and provide a smooth latching action, a quiet alternative to the traditional top trip catch.


Pullman Fixing Kits supplied separately to upgrade existing installations.

## PH.905 EMERGENCY EXIT WITH VERTICAL BOLTS - **FIXING KITS**




### **370PLTM** - PULLMAN FIXING KIT

Pullman fixing kit for timber and metal doors.



### **370PT** - PANIC BOLT FIXING KIT

Panic bolt fixing kit for timber doors.



### **370PM** - PANIC BOLT FIXING KIT

Panic bolt fixing kit for metal doors.

All BOSS exit devices are supplied with self-tapping screws suitable for timber and metal doorsets.

For customers who prefer machine screws, alternative fixing packs are available.

## PH.905 EMERGENCY EXIT WITH VERTICAL BOLTS - **INSTALLATION AND MAINTENANCE**

Panic and emergency exit hardware play a vital role in a building's escape route and it is important that these devices are installed, inspected and maintained regularly to ensure safety at all times.

### **Types of maintenance**

Much of the routine maintenance recommended consists of a combination of visual and mechanical checks, cleaning and lubrication. Look out for the icons opposite which provide a 'quick glance' reminder of the maintenance required.

### **Exit hardware**

All panic hardware installation will be operated by a horizontal "Push bar" or "Touch bar" which runs across the width of the door. The operating bar will be used to operate anything from a single rim latch to multipoint side or top/bottom latches.

Top and bottom latches on BOSS PH.9 panic exit hardware are operated by solid rods which are connected to the operating bar.

### **Visual checks**

Primarily making a visual check on the product and surrounding door/frame looking for wear, damage, and general condition.

### **Functional checks**

Consists of checking that the product operates properly without any binding or undue force required. Check that any seals or weatherstripping do not inhibit correct operation of the door.

### **Check fixings**

Fixings need to be checked regularly and tightened when necessary. Check that no projection of fixings prevents the door from swinging freely.

### **Lubricating**

Some products will benefit from periodic lubrication using a light machine oil or as instructed.

### **Cleaning**

Build up of grease, dust and harmful chemicals should be removed to prevent corrosion and maintain the product finish.




## **INSTALLATION**

Comprehensive installation instructions are provided with all BOSS PH.9 Series exit devices. To maximise the efficiency and life cycle of these products it is important to follow the installation guidance carefully to achieve an accurate installation. To meet the European standard, the door and frame must be in a good condition, correctly hung and not distorted. We recommend verifying the door construction before installation to ensure it allows for the use of the device.

## **MAINTENANCE AND CHECKING FUNCTION**

In view of the important role the panic and emergency exit device plays in maintaining the safety and security of your building and its occupants, it is recommended that routine maintenance checks are carried out at intervals of not more than 1 month by the occupier or their approved representative.

## PH.905 EMERGENCY EXIT WITH VERTICAL BOLTS - **EXIT HARDWARE MAINTENANCE**



### MONTHLY CHECKS

BOSS panic exit devices must be fitted to comply with the requirements of EN 1125 which states that the device should be easily operated by hand or body pressure in a panic situation. We suggest the following checks be made on all panic and emergency exit hardware:

- Inspect and operate the device to ensure all the components are in satisfactory working condition and operate as follows:
  1. After being pushed the 'Push bar' or 'Push Pad' should return automatically to its initial position.
  2. When pushed from the end casing side (hinge side of door) the latchbolt(s) should completely withdraw from their strikes as if it were pushed from the main casing side.

#### **IMMEDIATE EXIT MUST BE PERMITTED.**

3. With the door closed, the latchbolts should be fully engaged into their strikers. They should not withdraw if pushed but should only withdraw if operated by the 'Push bar'.
  4. If necessary upper and lower pullman latches can be adjusted to ensure the accuracy of latching.
- Inspect strikers and ensure they are clean and free from obstruction.
  - Ensure the door closes fully into the frame and there are no obstructions.
  - Check that the door has not become distorted in any way. If the door does not meet the frame stops and cannot be pulled in by the door closer the door may need to be replaced.
  - Check that the door hinges are operating smoothly and lubricate if necessary.
  - Check that the latches are operating freely. If necessary remove the end box covers and/or pullman latch covers and lubricate if necessary.
  - Check that all fixings are tight.

**To assist in keeping these products fully operational spare part kits are available.**

