38 -22 48583176 (A)

Left Hand Hung.



Fold Line Here.
(Top of Door)

446mm to Next Fixing Point.

This template covers track arm installation to 110°

2-4 Model		
N° of Turns	Direction	Size
1.1/2	-	2
0	*	3
3	+	4



Power Adjustment

* : FACTORY PRE-SET

EN1154		
Door Closer Power Size	Recommended Door Leaf Width Max mm	Test Door Mass (Kg)
1	750mm	20 Kg
2	850mm	40 Kg
3	950mm	60 Kg
4	1100mm	80 Kg
5	1250mm	100 Kg
6	1400mm	120 Kg

APPROVED PRODUCT
CF6141

CE 2812-CPR		Boss Door Controls Ltd 3-4 Rutherford Square Buncefield Industry Park Livingston EN54 9BU Scotland		TS6.224 certifire				CF 6141		UK CA 1121-CPR	
AD0300	20	FIG 1 EN 1154:1996+A1:2002	3	8	2/4	1	1	3		AD - UK AD8025	22

boss door controls

Right Hand Hung.

48583176 (A)



446mm to Next Fixing Point.

Fold Line Here.
(Top of Door)

This template covers track arm installation to 110°

2-4 Model		
N° of Turns	Direction	Size
1.1/2	-	2
0	*	3
3	+	4



Power Adjustment

* : FACTORY PRE-SET

EN1154		
Door Closer Power Size	Recommended Door Leaf Width Max mm	Test Door Mass (Kg)
1	750mm	20 Kg
2	850mm	40 Kg
3	950mm	60 Kg
4	1100mm	80 Kg
5	1250mm	100 Kg
6	1400mm	120 Kg

APPROVED PRODUCT
CF6141

CE 2812-CPR		Boss Door Controls Ltd 3-4 Rutherford Square Buncefield Industry Park Livingston EN54 9BU Scotland	TS6.224 certifire CF 6141						UKCA 1121-CPR	
AD0300	20	FIG 1 EN 1154:1996+A1:2002	3	8	2/4	1	1	3	AD - UK AD8025	22

boss door controls