Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

"BRITON 372 (See ANNEX A) 389 (See ANNEX B) 1438 (See ANNEX C) & BOSS PH.905 (See ANNEX A) PH.907 (See ANNEX B) PH.906 (See ANNEX C) Push Pad Range" Emergency Exit Devices

Intended use: For use on single and double leaf escape route doors, including fire resisting doors & Locked doors on escape routes.

Essential Characteristics	Performance	Harmonised Technical Specification
Mechanical Test Evidence : WIL 539076 / WIL 539077 / WIL 539078 / WIL 539079 / WIL 541902 Iss 2 / WIL 539080 / WIL 539081 / WIL 539081-1 & WIL 541969 **Fire Test Evidence : WF 127579 / WF 417359 / WF 417361 Iss 2 / WF 539511/R / WF 542544/R Iss 2 & WF 544056 Iss 1**		
Clause 4.2.1 Ability to release (for doors on escape routes) Release function Push pad Single doorset Double doorset Exposed edges and corners Push pad installation Operating element projection Operating element face (Push Pad) Push pad operating gap Test rod Push pad release operation Accessible gap Door free movement Top vertical bolt Keepers Keepers dimensions Door mass and dimensions Outside access device Release forces Security requirement	 < 1 sec Pass Pass Pass Pass Z < 250 mm W< 100mm Pass Pass Pass Pass Pass Pass Pass – **(Annex A Only)** Pass Pass – **(Annex A Only)** Door mass ≤ 200 Kg, door height ≤ 2500 mm, door width ≤ 1300 mm Pass Type B < 150 N Grade 4	**EN 179 : 2008**
Clause 4.2.1 Durability of ability to release against aging and degradation (for doors on escape routes) Corrosion resistance Temperature range Covers for vertical rods Lubrication Re-engagement force Durability Abuse resistance – Push Pad Abuse resistance –Vertical rod Final examination	 Grade 3 : 96 hours Operating forces at -10 C° and + 60 C° < 50% in excess of the operating forces at +20 C° NPD Lubrication every 20 000 cycles < 50 N Grade 7: 200 000 cycles 500 N & 1000N 500 N – **(Annex A Only)** Type B < 150 N	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Essential Characteristics	Performance	Harmonised Technical Specification
Clause 4.2.1 Self closing ability C (for fire/smoke doors on escape routes) Re-engagement force	< 50 N	**EN 179 : 2008**
Clause 4.2.1 Durability of self closing ability C against aging and degradation (for fire/smoke doors on escape routes) Durability Re-engagement force	Grade 7: 200 000 cycles < 50 N	
Clause 4.2.1 Resistance to fire E (integrity) and I (insulation) (for fire doors on escape routes) Suitability of panic exit devices for use on fire resisting doorsets assemblies – Additional requirements	Grade B: Suitable for use on fire/smoke door assemblies.	
Clause 4.1.25 Control of Dangerous substances	If a reference to dangerous substances is added in the table ZA.1, the following claim is suggested: Pass: the materials in the device do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Product Codes	Single Door (Standard Keeper)	Double Door (Standard Keepers)	Approved with Alternate Strike or Keeper			
			Briton 378 DDS Boss PH901 DDS	Briton 376 MDS Boss PH902 MDS	Briton 378 MDS Boss PH901 MDS	Briton 379 MDS Boss PH904 MDS
ANNEX A						
Briton 372	√	√	---------	√	---------	---------
Briton 372M	√	√	---------	√	---------	---------
Briton 372D	√	√	---------	√	---------	---------
Boss PH.905 with PH900PLTM	√	√	---------	√	---------	---------
Briton 372 with 370PLTM	√	√	---------	√	---------	---------
Boss PH.905	√	√	---------	√	---------	---------
Briton 372M with 370PLTM	√	√	---------	√	---------	---------
ANNEX B						
Briton 389.N	√	√	---------	---------	---------	√
Briton 389M.N	√	√	---------	---------	---------	√
Boss PH.907	√	√	---------	---------	---------	√
ANNEX C						
Briton 1438	√	√	√	---------	√	---------
Briton 1438M	√	√	√	---------	√	---------
Briton 1438D	√	√	√	---------	√	---------
Boss PH.906	√	√	√	---------	√	---------

Outside Access Devices	
Model Number	**Description**
Briton 1413.LE	Lever outside access device (Suitable for use with all Briton devices)
Briton 1413.KE	Knob outside access device (Suitable for use with all Briton devices)
Boss OAD.900LE	Lever outside access device (Suitable for use with all Boss devices)
Boss OAD.900KE	Knob outside access device (Suitable for use with all Boss devices)

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Accessories	
Briton 376/1001/SE	Main Box Assembly
Briton 376/1011/SE	End Box Assembly
Briton 378/1001/SE	Latch Box Assembly
Briton 376/416/50	End Plug
Briton 376/931/SE	Pullman Assembly x 1 for replacement
Briton 379/931/SS	Nightlatch lock case
Briton 379/1001/SE	Mortice latch Box Assembly
Boss PH902/1001/SIL	Main Box Assembly
Boss PH902/1011/SIL	End Box Assembly
Boss PH901/1001/SIL	Latch Box Assembly
Boss PH9/416/50	End Plug
Boss PH9/931/SIL	Pullman Assembly x 1 for replacement
Boss PH904/931/SS	Nightlatch lock case
Boss PH904/1001/SIL	Mortice latch Box Assembly
Briton 376ELTS/SE	Extra Long Shoot Bolts
Briton 376FFKP/ZP	Flush Face Keeper Plate
Briton 376/330/00	'Push Bar to Open' Label
Briton PH902ELTS/SIL	PH902 Extra Long Shoot Bolts
Briton PH902FFKP/ZP	PH902 Flush Face Keeper Plate
Briton PH9/330/00	'Push Bar to Open' Label
Cisa 0G500.50.12 SD1	Cisa C2000 Rim Cylinder nickle plated brass (For use on 1438 only)
Cisa 0G500.50.00 SD1	Cisa C2000 Rim Cylinder sanded brass (For use on 1438 only)
Briton 9260 Codelock	Lever Outside access device (Suitable for use with 372 & 1438 only)
Fixing Kits	
Briton 370PT	370 series Panic Bolt fixing kit (376/372/377) Timber Door
Briton 370PM	370 series Panic Bolt fixing kit (376/372/377) Metal Door
Briton 370PLT	370 series Emergency Exit latch fixing kit (1438/378/377) Timber Door
Briton 370PLM	370 series Emergency Exit latch fixing kit (1438/378/377) Metal Door
Briton 370EMT	370 series Emergency mortice latch fixing kit (379.N/389.N) Timber/Metal door
Briton 370PLTM	370 Series Panic Bolt Pullman fixing kit (376/372) Timber/Metal x2 pullmans plus instruction plus strikes/screws
Boss PH900PT	PH900 series Panic Bolt fixing kit (PH902/PH905/PH903) Timber Door
Boss PH900PM	PH900 series Panic Bolt fixing kit (PH902/PH905/PH903) Metal Door
Boss PH900PLT	PH900 series Emergency Exit latch fixing kit (PH906/PH901/PH903) Timber Door
Boss PH900PLM	PH900 series Emergency Exit latch fixing kit (PH906/PH901/PH903) Metal Door
Boss PH900EMT	PH900 series Emergency mortice latch fixing kit (PH904/PH907) Timber door
Boss PH900PLTM	PH900 Series Panic Bolt Pullman fixing kit (PH902/PH905) Timber/Metal x2 pullmans plus instruction plus strikes/screws

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Screw Packs	
Briton 376/920/ZP	370 Series (376, 372, 377) Timber door screw pack
Briton 376/919/ZP	370 Series (376M, 372M, 377M) Metal door screw pack
Briton 378/920/ZP	370 Series (378, 1438, 377) Timber door screw pack
Briton 378/919/ZP	370 Series (378M, 1438M, 377M) Metal door screw pack
Briton 379/940/ZP	370 Series (379, 389) Timber door screw pack
Briton 379/919/ZP	370 Series (379M, 389M) Metal door screw pack
Briton 376/940/ZP	376 Pullman timber door screw pack
Briton 376/949/ZP	376 Pullman Metal door screw pack
Boss PH902/920/ZP	PH900 Series (PH902, PH905, PH903) Timber door screw pack
Boss PH902/919/ZP	PH900 Series (PH902M, PH905M, PH903M) Metal door screw pack
Boss PH901/920/ZP	PH900 Series (PH901, PH906, PH903) Timber door screw pack
Boss PH901/919/ZP	PH900 Series (PH901M, PH906M, PH903M) Metal door screw pack
Boss PH904/940/ZP	PH900 Series (PH904, PH907) Timber door screw pack
Boss PH904/919/ZP	PH900 Series (PH904M, PH907M) Metal door screw pack
Boss PH902/940/ZP	PH902 Pullman timber door screw pack
Boss PH902/949/ZP	PH902 Pullman Metal door screw pack

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-ABB0020

Placed on the market under the Name of:

Allegion Safety & Security Solutions Limited
Orbital 60
Dumers Lane
Bury
BL9 9UE
United Kingdom

and produced in the manufacturing plant:

E018761-6

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the assessment and verification of constancy of performance and the performances described in Annex ZA of the standard(s)

EN 179: 2008

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **26/08/2009** and revised on **17/06/2026** and will remain valid as long as neither the harmonised standard, the construction product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

CE Marking certificate valid to: **02/04/2029**

ERO Project Reference: **ERO 034621 P3355**

Paul Duggan
Certification Manager

CSF408-NL 8.0